

2017 BUXTON RACEWAY STREET BANGERS

Also applies to Ladies Bangers

Rules Last updated 7th January 2017 E&OE

Any steel bodied car up to 1800cc as manufactured. No 4x4 or people carrier

If car came on carbs stays on carbs if it comes on injection it stays on injection. NO EXCUSES

Honda powered cars are restricted to 1500cc and must remain on injection. All ECU's must be available to be checked at scrutineering. **No Honda powered cars on carbs will be allowed.**

STRICTLY NO WELDING

BODYWORK:

All Bodywork must remain standard, no cutting or folding of wings.

All plastic bumpers must be removed, along with any spoilers.

Only seatbelt is allowed to secure boot and doors. No bolts in doors or arches.

INTERIOR:

All seats and interior must be removed and stripped.

Drivers seat must have padding around seat and must be tied to roll cage

Dashboards can be removed.

DOOR PLATE MUST BE FITTED

A steel plate 10" to 15" deep 3/8 – 3/4" thick must be bolted over the drivers door. This must be fitted with a minimum of 3" and a maximum of 6" past the A & B pillars at each end securely bolted with a minimum of 4 bolts. There must be at least 1 bolt through the A pillar and one must be through the B pillar or through the roll cage. The bolt size must be at least 16mm studding or bolt (Only flat plate is allowed, no channel, angle or corrugated steel allowed). 12mm is the smallest size bolt allowed on all other bolts except A & B pillar.

H FRAME MUST BE FITTED

The Roll Bar must be one complete frame, and constructed from steel. All frames must be welded. Roll bars to be securely bolted to the floor and roof, with four minimum 12mm bolts and suitable washers to the floor and two similar size bolts and washers to the roof. In cases where sunroof was originally in car and a roof plate has to be fitted then you may bolt your roll bars through it

The frame may be two uprights with crossbar welded. Uprights must have 4" square steel plates welded to the base to stop pushing them through the floor. The minimum thickness of the plates to be 5mm. Similar size plates may also be used to the roof for fixing purposes.

At least one, maximum two, crossbars must be used to reach to doors or pillars and must have 4" plates welded to both ends to stop them punching through doors. At least one of the crossbars must be at roof level. Scaffolding poles, Acrows, and related clamps CAN NO LONGER BE USED.

Roll bar materials: Minimum 2"x2" box section. Wall thickness to be minimum 3mm.

Suspension may be lowered by heating or cutting the springs.

A Banger Fuel tank must be used and fitted to roll cage. As per the National Banger rules.

Original Fuel tank must be removed

Continued to Page 2.....

No passenger side plates.

Radiator must remain in original place for start of first race but then may be moved anywhere under bonnet.

At any time following a meeting a model of car can be banned if it is dominating the formula. Don't stockpile cars.

No team colours.

Nudge and spin – no spinning to fence, no stationary car hits and certainly no follow ins. 1 month ORCi ban for first illegal move and 3 month for second. 3rd instance within 12 months will result in a full ban from the formula. These are minimum bans excessive hits may result in larger penalties

TYRES:

Must be as come on the car. No lower profile than 50. No Competition Tyres will be allowed. NO federals, rainsports, nankangs, Michelins or Bridgestones

SAFETY EQUIPMENT:

Fireproof Neck braces are recommended, and if used must be marked appropriately.

Overalls

Drivers must wear bright coloured racing overall type clothing of flame retardant Proban or a higher specification material and marked accordingly. Overalls must be maintained in a clean and tidy condition when in view of the public. If wet weather clothing is used this must be worn in addition to, and over the top of, and not instead of the regulation overall type clothing described above.

Helmets

Helmets must be of a minimum standard as directed by British Oval Racing Safety Executive (B.O.R.S.E). These are, FIA8860-2004, Snell SA2005, Snell SA2010, SFI Foundation 31.1A, SFI Foundation 31.2A. The E2205 European standard helmet may be used in Fiberglass, Carbon or Tri-Composite form only i.e. NO POLYCARBONATE helmets are allowed. It is important that the helmet fits the driver correctly. Shatterproof goggles/visors must be worn although tinted visors are not advisable. Your helmet must display the current ORCi (ORC10) sticker

Gloves/ Balaclava

All drivers must wear fire proof gloves and balaclava, minimum Proban

Following the final of the meeting Buxton Raceway can purchase your car for £150. All that can be removed is the door plate, h frame, fuel tank, fuel lines and kill switch/ ignition switches. This is to stop people spending money on engines and tyres and to even it all for all drivers. Refusal to sell the car will tell Buxton Raceway the car is illegal and you will receive a 12 month ORCi ban.

There will be no prize money for this formula as every driver who books in and turns up will receive £10 start money.

Book in via:

Phone: 01663 732525

Email: nikeastwood@buxtonraceway.com

Facebook: Buxton Raceway Facebook Group